

TYPICAL APPLICATION



Automotive



Com. Vehicle



Construction



Electrical



Energy



Industrial



Mass Transport



Sanitary

PRODUCT DESCRIPTION

menzolit[®] BMC 9100 is a bulk moulding compound based on unsaturated polyester resin. The product is a high - performance BMC containing 20 % of recycled components glass fibre reinforced and contains mineral fillers. In case of fire the product doesn't melt, neither does it form droplets nor is smoke generation excessive. The material is injection moulded in heated steel moulds. It is recommended to work with chrome plated tools. It does not contain any halogens nor any candidates from the REACH SVHC list.

PRODUCT SPECIFICATION

menzolit[®] BMC 9100 is tailored for automotive and commercial vehicle parts for front lighting systems.

TYPICAL PROPERTIES	Standard	Units	
Density	ISO 1183	g/cm ³	1,9
Shrinkage	ISO 2577	%	0,00
Heat Distortion Temp.	EN ISO 75-2	°C	>200
Continuous Service Temp.	Menzolit	°C	150
Young's Modulus	EN ISO 527-4	GPa	14
Tensile Strength	EN ISO 527-4	MPa	25
Flexural Strength	EN ISO 14125	MPa	>90
Flex Modulus	EN ISO 14125	GPa	>12
Impact Strength	EN ISO 179	kJ/m ²	>15
Glow Wire Index	IEC 60707-3	°C	
Fire Retardancy	UL 94		
Surface Resistivity	IEC 60093	Ohm	
Comparative Tracking Index	IEC 60112	Level	
Water Absorption	ISO 62	%	< 0,5

FORM of SUPPLY

menzolit[®] BMC 9100 is packaged in styrene tight bags and placed in cardboard or wooden boxes. Various kinds of packaging available. For alternative packaging please contact our technical service team. Available in natural colours.